

KM-901M_J 11/16/17 Item # 13213

WxDxH 30" x 273/8" x 321/2"

Shipping Dimensions 33^{1/4}" x 33^{1/2}" x 38^{1/2}"

KM Edge DESIGN

KM-901MAJ

Air-Cooled Shown on optional bin B-900

> KM-901MWJ Water-Cooled

KM-901MRJ

Remote Air-Cooled 1 Phase

KM-901MRJ3

Remote Air-Cooled 3 Phase

















Project: _ Qty: ΔΙΔ#٠

Features

Item #:

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaver™ design CycleSave



- Up to 950 lbs. of ice production per 24 hours
- · Durable stainless steel exterior
- Protected by H-GUARD Plus —GUARD **Antimicrobial Agent**
- EverCheck™ alert system evercheck
- Removable air filters (Air-cooled model only)
- R-404A Refrigerant

Available on Bins:

B-700PF/SF B-900PF/SF B-1300SS B-500PF/SF B-800PF/SF B-1150SS B-1500SS*

Top kit may be required. See Bin Spec Sheets. *Two unit application only.

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator.


5 Year Parts on Compressor; air-cooled condenser coil.

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

			ICE PRODUCTION		WATER USAGE			ELECTRICAL*														
Condenser		Model	Air / Wat Lbs. per 70°/ 50°F		Potable Gal. per 100 lbs. 90°/ 70°F	Condenser Gal. per 100 lbs. 90°/ 70°F	kWh Used per 100 lbs. 90°/ 70°F	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Circuit Wires (including ground)	Heat Rejection BTU/hr.	Refrigerant Charge Amount	Net / Ship Weight (lbs.)								
	Air	KM-901MAJ	905	753	22.0	N/A	5.0	20A	13A	208-230/60/1	4	13,000	3 lb. 4.9 oz.	228 / 260								
1 Phase	Water	KM-901MWJ	950	870	16.0	113	3.6	20A	10A	208-230/60/1	4	12,700	1 lb. 14 oz.	218 / 250								
	Remote	KM-901MRJ	904	853	16.0	N/A	4.5	20A	12A	208-230/60/1	4	12,500	12 lb. 5.5 oz.†	218 / 250								
3 Phase	Remote	KM-901MRJ3	927	830	15.0	N/A	4.4	20A	7.1A	208-230/60/1	4	12,000	12 lb. 5.5 oz.†	240 / 250								
+16			C	110 5000				!	-11	†(with condensor)												

*If neutral is not available transformer kit (HS-5030) is required. Refer to instruction manual for installation and electrical requirements.

KM Edge Cube Dimensions[†]



* approximate size in inches, image not to scale

Operating Limits

Ambient Temp Range

45 - 100°F 45 - 90°F

Water Temp Range

10 - 113 PSIG

 Water Pressure · Voltage Range

187-253V

Service


- · Panels easily removed and all components accessible for service.
- Allow 12" (30 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance and/or service should they be required.


- Icemaker Water Supply Line: Min.1/4" Nominal ID Copper Water **Tubing or Equivalent**
- Icemaker Drain Line: Min. 3/4" Nominal ID Hard Pipe or Equivalent Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Min. 1/4" Nominal ID Copper Water Tubing or Equivalent
- Condenser Drain/Return Line: Min. 1/4" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent


Water Filter

Please refer to water filter spec sheet for recommended configurations. Hoshizaki reserves the right to change specifications without notice. Front













AIR-COOLED


| CEMMER WATER INLET | ICEMMER |












AIR-COOLED


WATER-COOLED

REMOTE AIR-COOLED

URC-14F Remote Condenser (Sold Separately)
(W x D x H) 35 11/16 x 14 1/16 x 36 1/2

For Use with KM-901MRJ(3)





AIR-COOLED

[17-1/2]

[5-7/8]

WATER-COOLED REMOTE AIR-COOLED